



1130 Medium Duty General Purposes Caster Series


AQPU (grey) Wheel Diameter × Wheel Width 75 x 31mm

EAN
TW-4113003002030

Swivel Caster with Riveted Stamping Fork—Ø11x38L Zine-Plated, Mounting Type - Cylindrical Stem, brass buckle, and plastic sleeve Aluminum core with High Quality Polyurethane Wheel Tread Gray, Bearing—Ball Bearings.

Wheel tread: high quality polyurethane
Wheel Center: aluminum core

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

☒ Imperial ☐ Metric	
Wheel Diameter	3 "
Wheel Width	1-1/4 "
Wheel Bearing	Wheels With Ball Bearings
Diameter	3/8 "
Stem Hole Spec	1-1/2 "
Offset	1-3/8 "
Swivel Interference	5-13/16 "
Overall Height	4-1/16 "
Swivel Radius	2-15/16 "
Hardness Of Tread	77±5° Shore A
Load Capacity (Dynamic)	353lbs
Load Capacity (Static)	529lbs
Temperature	-4°F to +158°F
Fork Type	Swivel Caster
Stainless	N/A
Electrical Conductivity	N/A
Anti-Static	N/A
Weight	1.1lbs
Standard	ISO22883


Advantages at a glance

Rolling Resistance	● ● ● ● ●
Operating Noise	● ● ● ● ●
Floor Surface Preservation	● ● ● ● ●

Dimensions



Mounting



* For any deviation between metric and imperial spec, please refer to the metric spec.