

1130 Medium Duty General Purposes Caster Series




PPR (red) Wheel Diameter × Wheel Width 75 x 31mm

EAN  
TW-4113003004106

Casters with Side Brakes and With locking system. Threaded Stem Riveted Pressed Fork – 3/8-16 threads.  
Zine-Plated, Mounting Type - Threaded Stem.  
High-Quality Impact-Resistant Polypropylene Wheel Center, High-Quality Reinforced Polypropylene Rubber (TPR) Wheel Tread.  
Red color, Bearing – Ball Bearing.

Wheel tread: Thermoplastic rubber elastomer (TPR)  
Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

|                                                                        |                               |
|------------------------------------------------------------------------|-------------------------------|
| <input checked="" type="radio"/> Metric <input type="radio"/> Imperial |                               |
| Wheel Diameter                                                         | 75mm                          |
| Wheel Width                                                            | 31mm                          |
| Wheel Bearing                                                          | Wheels With Ball Bearings     |
| Threaded Stem                                                          | 3/8 " -16牙                    |
| Threaded Size                                                          | 32mm                          |
| Offset                                                                 | 35mm                          |
| Swivel Interference                                                    | 150mm                         |
| Overall Height                                                         | 108mm                         |
| Swivel Radius                                                          | 75mm                          |
| Hardness Of Tread                                                      | 82±5° Shore A                 |
| Load Capacity (Dynamic)                                                | 70kgs                         |
| Load Capacity (Static)                                                 | 105kgs                        |
| Temperature                                                            | -20°C to +60°C                |
| Fork Type                                                              | Swivel Caster With Side Brake |
| Stainless                                                              | N/A                           |
| Electrical Conductivity                                                | N/A                           |
| Anti-Static                                                            | N/A                           |
| Weight                                                                 | 0.60kgs                       |
| Standard                                                               | ISO22883                      |


Advantages at a glance

|                            |           |
|----------------------------|-----------|
| Rolling Resistance         | ● ● ● ● ○ |
| Operating Noise            | ● ● ● ● ○ |
| Floor Surface Preservation | ● ● ● ● ● |

Dimensions



Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.