

1153 Heavy Duty 2" Wide General Purposes Caster Series




QPU (brown) Wheel Diameter × Wheel Width 150 x 42mm

EAN  
TW-4115306004087

Casters with a front brake and With locking system. Top Plate Riveted and Stamping. Zine-Plated, Mounting Type - Top Plate. Cast Iron core with High Quality Polyurethane Wheel Tread. Brown color, Bearing—Ball Bearings.

Wheel tread: high quality polyurethane  
Wheel Center: iron core/cast iron core

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

|                                                                        |                                |
|------------------------------------------------------------------------|--------------------------------|
| <input checked="" type="radio"/> Metric <input type="radio"/> Imperial |                                |
| Wheel Diameter                                                         | 150mm                          |
| Wheel Width                                                            | 42mm                           |
| Wheel Bearing                                                          | Wheels With Ball Bearings      |
| Plate Size                                                             | 137 x 105mm                    |
| Bolt Hole Spacing                                                      | 105 x 77.5mm                   |
| Plate Hole                                                             | 13.5 x 11mm                    |
| Offset                                                                 | 60mm                           |
| Swivel Interference                                                    | 330mm                          |
| Overall Height                                                         | 190mm                          |
| Swivel Radius                                                          | 165mm                          |
| Hardness Of Tread                                                      | 92±5° Shore A                  |
| Load Capacity (Dynamic)                                                | 350kgs                         |
| Load Capacity (Static)                                                 | 525kgs                         |
| Temperature                                                            | -20°C to +70°C                 |
| Fork Type                                                              | Swivel Caster With Front Brake |
| Stainless                                                              | N/A                            |
| Electrical Conductivity                                                | N/A                            |
| Anti-Static                                                            | N/A                            |
| Weight                                                                 | 3.30kgs                        |
| Standard                                                               | ISO22883                       |


Advantages at a glance

|                            |           |
|----------------------------|-----------|
| Rolling Resistance         | ● ● ● ● ● |
| Operating Noise            | ● ● ● ● ● |
| Floor Surface Preservation | ● ● ● ● ● |

Dimensions



Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.