

1110-YOYO YOYO Series-Light Duty Twin Wheel Caster Series (All Plastic)




Yoyo Wheel (black dark gray) Wheel Diameter x Wheel Width 65 x 18mm

EAN

YJ-11100250244123

Single Brake locking system and a Fork-Riveted, injection-molded Fork, reinforced Polypropylene Fork with Fork-mount (3T) Mounting Type system Polypropylene (PP) Wheel Center, polyvinyl chloride (PVC) tread Dark gray, Anti-thread wheel cover.



Wheel Tread: PVC polyvinyl chloride
Wheel Center: PP polypropylene

Drawings are for reference only and may differ from the product

Picture may differ from original product

Technical Data

Imperial Metric

Wheel Diameter 2-9/16

Wheel Width 2-3/8

Wheel Bearing Wheel With Plain Bearing

Plate Size 3-3/4 " x 2-1/2 "

Bolt Hole Spacing 3 " x 1-13/16 "

Plate Hole 3/8 " x 3/8 "

Offset 13/16 "

Swivel Interference 6 "

Overall Height 3-1/4 "

Swivel Radius 2-3/8 "

Hardness Of Tread 95±5° Shore A

Load Capacity (Dynamic) 99lbs

Load Capacity (Static) 149lbs

Temperature -4°F to +140°F

Fork Type Swivel Caster With Wheel Brake

Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 0.7lbs

Standard ISO22883


Advantages at a glance

Rolling Resistance • • • •


Operating Noise • • • •

Floor Surface Preservation • • • •

Dimensions



Mounting



* For any deviation between metric and imperial spec, please refer to the metric spec.

© Copyright 2025 Dersheng International www.dersheng.com