1110-YOYO YOYO Series-Light Duty Twin Wheel Caster Series (All Plastic)

Dersheng Casters Keep Rolling

Yoyo Wheel (light dark gray) Wheel Diameter x Wheel Width 72.8 x 20mm

EAN

YJ-11100300248213

Single Brake locking system, insert-Riveted, injection-molded Fork (\emptyset 11 x 38L). reinforced Polypropylene Fork, insert-type Mounting Type mechanism. Polypropylene (PP) core, polyvinyl chloride (PVC) tread. White-dark gray, wheel with Plain Bearing design.

Wheel Tread: PVC polyvinyl chloride Wheel Center: PP polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data

● Imperial ○ Metric

Wheel Diameter 2-15/16
Wheel Width 2-1/2 "

Wheel Bearing Wheel With Plain Bearing

Diameter 3/8 "

Stem Hole Spec 1-1/2 "

Offset 1 "

Swivel Interference 6-13/16 "

Overall Height 3-3/16 "

Swivel Radius 3-7/16 "
Hardness Of Tread 95±5° Shore A

Load Capacity (Dynamic) 99lbs

Load Capacity (Static) 149lbs

Temperature -4°F to +140°F

Fork Type Swivel Caster With Wheel Brake

Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 0.6lbs

Standard ISO22883

Advantages at a glance


Rolling Resistance

Operating Noise


Floor Surface Preservation

• • • • •

Dimensions



Mounting



 $[\]boldsymbol{\ast}$ For any deviation between metric and imperial spec, please refer to the metric spec.