



1110-2 Light Duty Wire & Shelving/Display Series

PU (Black Transparent) Wheel Diameter × Wheel Width 76 × 23.5mm

EAN

YJ-11100300955014

Swivel Caster, thread-Riveted Stamping Fork—M8-P1.25 Surface electroplating, Mounting Type - Threaded Stem Polypropylene core, High Quality Polyurethane tread Translucent black, Bearing—Ball Bearing.

Wheel Tread: high quality polyurethane
Wheel Center:Polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

☒ Imperial ☐ Metric	
Wheel Diameter	3 "
Wheel Width	15/16 "
Wheel Bearing	Wheels With Ball Bearings
Threaded Stem	M8-P1.25
Threaded Size	5/8 "
Offset	7/8 "
Swivel Interference	4-11/16 "
Overall Height	3-7/8 "
Swivel Radius	2-3/8 "
Hardness Of Tread	80±5° Shore A
Load Capacity (Dynamic)	110lbs
Load Capacity (Static)	165lbs
Temperature	-4°F to +158°F
Fork Type	Swivel Caster
Stainless	N/A
Electrical Conductivity	N/A
Anti-Static	N/A
Weight	0.5lbs
Standard	ISO22883


Advantages at a glance

Rolling Resistance	● ● ● ● ●
Operating Noise	● ● ● ● ●
Floor Surface Preservation	● ● ● ● ●

Dimensions



Mounting



* For any deviation between metric and imperial spec, please refer to the metric spec.