

1110-YOYO YOYO Series-Light Duty Twin
Wheel Caster Series (All Plastic)

Yoyo Wheel (black dark gray) Wheel Diameter x Wheel Width 100 x 22mm


EAN

YJ-11100400245013

Swivel Caster, thread-Riveted injection-molded Fork—M8-P1.75 reinforced Polypropylene Fork, Mounting Type - Threaded Stem Polypropylene (PP) core, polyvinyl chloride (PVC) tread Dark gray, Bearing—Ball Bearing.

Wheel Tread: PVC polyvinyl chloride
Wheel Center: PP polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

☒ Metric ☐ Imperial	
Wheel Diameter	100mm
Wheel Width	68mm
Wheel Bearing	Wheels With Ball Bearings
Threaded Stem	M8-P1.75
Threaded Size	15mm
Offset	32mm
Swivel Interference	176mm
Overall Height	108.5mm
Swivel Radius	88mm
Hardness Of Tread	95±5° Shore A
Load Capacity (Dynamic)	100kgs
Load Capacity (Static)	150kgs
Temperature	-20°C to +60°C
Fork Type	Swivel Caster
Stainless	N/A
Electrical Conductivity	N/A
Anti-Static	N/A
Weight	0.48kgs
Standard	ISO22883


Advantages at a glance

Rolling Resistance	• • • • •
Operating Noise	• • • • •
Floor Surface Preservation	• • • • •

Dimensions



Mounting



* For any deviation between metric and imperial spec, please refer to the metric spec.