

1110-YOYO YOYO Series-Light Duty Twin  
Wheel Caster Series (All Plastic)



Yoyo Wheel (black dark gray) Wheel Diameter x Wheel Width 100 x 22mm


EAN

YJ-11100400248013

Single Brake locking system, insert-Riveted, injection-molded Fork (Ø 11 x 22L). reinforced Polypropylene Fork, insert-type Mounting Type mechanism. Polypropylene (PP) Wheel Center, polyvinyl chloride (PVC) tread. Dark gray, Bearing: Ball Bearing.

Wheel Tread: PVC polyvinyl chloride  
Wheel Center: PP polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

|                                                                        |                                |
|------------------------------------------------------------------------|--------------------------------|
| <input checked="" type="radio"/> Metric <input type="radio"/> Imperial |                                |
| Wheel Diameter                                                         | 100mm                          |
| Wheel Width                                                            | 68mm                           |
| Wheel Bearing                                                          | Wheels With Ball Bearings      |
| Diameter                                                               | 11mm                           |
| Stem Hole Spec                                                         | 22mm                           |
| Offset                                                                 | 32mm                           |
| Swivel Interference                                                    | 212mm                          |
| Overall Height                                                         | 105.5mm                        |
| Swivel Radius                                                          | 106mm                          |
| Hardness Of Tread                                                      | 95±5° Shore A                  |
| Load Capacity (Dynamic)                                                | 100kgs                         |
| Load Capacity (Static)                                                 | 150kgs                         |
| Temperature                                                            | -20°C to +60°C                 |
| Fork Type                                                              | Swivel Caster With Wheel Brake |
| Stainless                                                              | N/A                            |
| Electrical Conductivity                                                | N/A                            |
| Anti-Static                                                            | N/A                            |
| Weight                                                                 | 0.51kgs                        |
| Standard                                                               | ISO22883                       |


Advantages at a glance

|                            |           |
|----------------------------|-----------|
| Rolling Resistance         | ● ● ● ● ● |
| Operating Noise            | ● ● ● ● ● |
| Floor Surface Preservation | ● ● ● ● ● |

Dimensions



Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.