1111 Institutional Caster Series

Dersheng Casters Keep Rolling

Rubber Wheel Diameter × Wheel Width 75 x 30mm


EAN

YJ-11110300062013

Swivel Caster, Top Plate Riveted Stamping Fork - high-grade hole Surface Zine-Plated, Mounting Type - Top Plate Reinforced Polypropylene, High-Quality Resilient Rubber Wheel Tread Wheel - Anti-thread wheel cover

Wheel Tread: high quality elastic rubber Wheel Center: Thermoplastic (PA6)

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data

Swivel Radius

● Imperial ○ Metric

3 " Wheel Diameter

1-3/16 " Wheel Width

Wheel Bearing Wheel With Plain Bearing

3-13/16 " x 2-7/8 " Plate Size **Bolt Hole Spacing** 3 " x 1-13/16 "

1/2 " x 3/8 " Plate Hole Offset 1-1/2 "

6 " Swivel Interference 4-1/2 " Overall Height 3 "

Hardness Of Tread 80±5° Shore A

Load Capacity (Dynamic) 154lbs Load Capacity (Static) 231lbs

-4°F to +248°F Temperature Fork Type **Swivel Caster**

Stainless N/A **Electrical Conductivity** N/A N/A Anti-Static Weight 1.7lbs Standard ISO22883


Advantages at a glance


Rolling Resistance

Operating Noise


Floor Surface Preservation • • • • •

Dimensions





Mounting



^{*} For any deviation between metric and imperial spec, please refer to the metric spec.