1111 Institutional Caster Series



PPR (Pearlescent dark gra) Wheel Diameter × Wheel Width 75 x 31mm

EAN


YJ-11110300269013

Castors with Side Brakes and Locking system. Single Bolthole Fork - ∅12.5 Surface Zine-Plated, Mounting Type - Single Bolthole device High-quality Impact Resistance Polypropylene Wheel Center, High-Quality Thermoplastic Rubber (TPR) Wheel Tread Dark gray, Bearing - Ball Bearings.

Wheel tread: Thermoplastic rubber elastomer (TPR)

Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data

● Metric ○ Imperial

Wheel Diameter 75mm
Wheel Width 31mm

Wheel Bearing Wheels With Ball Bearings

Single Bolt HoleCentre Hole 12.5mm

Offset 37mm

Swivel Interference 158mm

Overall Height 108mm

Swivel Radius 79mm

Hardness Of Tread 82±5° Shore A

Load Capacity (Dynamic) 90kgs

Load Capacity (Static) 135kgs

Temperature -20°C to +60°C

Fork Type Swivel Caster With Side Brake

Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 0.64kgs

Standard ISO22883

Advantages at a glance

Rolling Resistance


 \bullet \bullet \bullet \circ


Operating Noise

• • • • 0


Floor Surface Preservation • • • • •

Dimensions





Mounting



 $^{{}^{*}}$ For any deviation between metric and imperial spec, please refer to the metric spec.