1111 Institutional Caster Series



PPR (Pearlescent dark gra) Wheel Diameter × Wheel Width 75 x 31mm

EAN


YJ-11110300269013

Castors with Side Brakes and Locking system. Single Bolthole Fork - ∅12.5 Surface Zine-Plated, Mounting Type - Single Bolthole device High-quality Impact Resistance Polypropylene Wheel Center, High-Quality Thermoplastic Rubber (TPR) Wheel Tread Dark gray, Bearing - Ball Bearings.

Wheel tread: Thermoplastic rubber elastomer (TPR)

Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data

● Imperial ○ Metric

Wheel Diameter 3 "

Wheel Width 1-1/4 "

Wheel Bearing Wheels With Ball Bearings

Single Bolt HoleCentre Hole 1/2 "

Offset 1-1/2 "

Swivel Interference 6-5/16 "

Overall Height 4-5/16 "

Swivel Radius 3-1/8 "

Hardness Of Tread 82±5° Shore A

Load Capacity (Dynamic) 198lbs

Load Capacity (Static) 298lbs

Temperature -4°F to +140°F

Fork Type Swivel Caster With Side Brake

Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 1.4lbs

Standard ISO22883

Advantages at a glance

Rolling Resistance


• • • • 0


Operating Noise

• • • • 0


Floor Surface Preservation • • • • •

Dimensions





Mounting



 $^{{}^{*}}$ For any deviation between metric and imperial spec, please refer to the metric spec.