



1111 Institutional Caster Series

PP (black) Wheel Diameter x Wheel Width 75 x 32mm


EAN

YJ-11110300296023

Side Brake Locking system. Thread-Riveted Fork— 3/8"-16 Extended control lever surface, Mounting Type - Threaded Stem Polypropylene Wheel Center and Wheel Tread Black, wheels—Plain Bearing.

Wheel tread: PP polypropylene
Wheel Center: PP polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

☒ Metric ☐ Imperial	
Wheel Diameter	75mm
Wheel Width	32mm
Wheel Bearing	Wheel With Plain Bearing
Threaded Stem	3/8 " -16
Threaded Size	25mm
Offset	37mm
Swivel Interference	158mm
Overall Height	112mm
Swivel Radius	79mm
Hardness Of Tread	65±5° Shore D
Load Capacity (Dynamic)	90kgs
Load Capacity (Static)	135kgs
Temperature	-10°C to +60°C
Fork Type	Swivel Caster With Side Brake
Stainless	N/A
Electrical Conductivity	N/A
Anti-Static	N/A
Weight	0.62kgs
Standard	ISO22883


Advantages at a glance

Rolling Resistance	● ● ● ● ●
Operating Noise	● ● ● ○ ○
Floor Surface Preservation	● ● ● ○ ○

Dimensions



Mounting



* For any deviation between metric and imperial spec, please refer to the metric spec.