1111 Institutional Caster Series

Dersheng Casters Keep Rolling

Phenolic (black) Wheel Diameter × Wheel Width 100 x 34mm


EAN

YJ-11110400251033

Rigid castor, Stamping Fabricated Caster Fork - 75 x 45 mm (3" x 1-3/4") Bolt Hole Spacing Surface Zine-Plated, Mounting Type - Top Plate Wheel Tread And Wheel Center Made Of Compression Molded Phenolic Resin Filled With Macerated fabric Black, wheel - Anti-thread wheel cover.

Tread: Compressed synthetic resin impregnated with fabric Wheel Center: Compressed synthetic resin impregnated with fabric

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data

● Imperial ○ Metric

Wheel Diameter 4 "

Wheel Width 1-3/8 "

Wheel Bearing Wheel With Plain Bearing

 Plate Size
 3-7/8 " x 3 "

 Bolt Hole Spacing
 3 " x 1-13/16 "

 Plate Hole
 3/8 " x 3/8 "

 Overall Height
 5-1/2 "

Hardness Of Tread 80±5° Shore D

Load Capacity (Dynamic) 298lbs

Load Capacity (Static) 446lbs

Temperature -4°F to +302°F
Fork Type Rigid Caster

Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 1.1lbs

Standard ISO22883


Advantages at a glance


Rolling Resistance

Operating Noise


Floor Surface Preservation • • • • •

Dimensions





Mounting



^{*} For any deviation between metric and imperial spec, please refer to the metric spec.