



1111 Institutional Caster Series

PPR (Pearlescent dark gray) Wheel Diameter × Wheel Width 100 x 31mm


EAN

YJ-11110400262013

Swivel castor, Fork Riveted Stamping Fork - 75 x 45 mm (3" x 1-3/4") Bolt Hole Spacing  
Surface Zine-Plated, Top Plate Mounting Type Impact resistant High-quality Impact  
Resistance Polypropylene Wheel Center,High-Quality Thermoplastic Rubber (TPR) Wheel  
Tread Pearl grey, Bearing - Ball Bearing.

Wheel tread: Thermoplastic rubber elastomer (TPR)  
Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

|                                                                        |                           |
|------------------------------------------------------------------------|---------------------------|
| <input checked="" type="radio"/> Metric <input type="radio"/> Imperial |                           |
| Wheel Diameter                                                         | 100mm                     |
| Wheel Width                                                            | 31mm                      |
| Wheel Bearing                                                          | Wheels With Ball Bearings |
| Plate Size                                                             | 95 x 72.5mm               |
| Bolt Hole Spacing                                                      | 75 x 45mm                 |
| Plate Hole                                                             | 11.3 x 8.8mm              |
| Offset                                                                 | 43mm                      |
| Swivel Interference                                                    | 190mm                     |
| Overall Height                                                         | 137mm                     |
| Swivel Radius                                                          | 95mm                      |
| Hardness Of Tread                                                      | 82±5° Shore A             |
| Load Capacity (Dynamic)                                                | 100kgs                    |
| Load Capacity (Static)                                                 | 150kgs                    |
| Temperature                                                            | -20°C to +60°C            |
| Fork Type                                                              | Swivel Caster             |
| Stainless                                                              | N/A                       |
| Electrical Conductivity                                                | N/A                       |
| Anti-Static                                                            | N/A                       |
| Weight                                                                 | 0.77kgs                   |
| Standard                                                               | ISO22883                  |


Advantages at a glance

|                            |           |
|----------------------------|-----------|
| Rolling Resistance         | ● ● ● ● ○ |
| Operating Noise            | ● ● ● ● ○ |
| Floor Surface Preservation | ● ● ● ● ● |

Dimensions



Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.