1111 Institutional Caster Series

Dersheng Casters Keep Rolling

PAU (grey) Wheel Diameter × Wheel Width 125 x 31mm

EAN


YJ-11110500321013

Rigid castor, Stamping Fabricated Caster Fork - 75 x 45 mm (3" x 1-3/4") Bolt Hole Spacing Surface Zine-Plated, Top Plate Mounting Type Reinforced Polypropylene, High Quality Polyurethane Wheel Tread Grey, Bearing - Ball Bearing.

Wheel tread: Made of high quality polyurethane

Wheel Center: Thermoplastic (PA6)

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data

● Imperial ○ Metric

Wheel Diameter 5 "

Wheel Width 1-1/4 "

Wheel Bearing Wheels With Ball Bearings

Plate Size 3-7/8 " x 3 "

Bolt Hole Spacing 3 " x 1-13/16 "

Plate Hole 9/16 " x 3/8 "

Overall Height 6-3/8 "

Hardness Of Tread 94±5° Shore A

Load Capacity (Dynamic)287lbsLoad Capacity (Static)430lbsTemperature-4°F to +158°FFork TypeRigid Caster

Fork Type Rigid Cast
Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 1.6lbs

Standard ISO22883

Advantages at a glance

Rolling Resistance


 \bullet \bullet \bullet \circ


Operating Noise

• • • 0


Floor Surface Preservation • • • • •

Dimensions





Mounting



^{*} For any deviation between metric and imperial spec, please refer to the metric spec.