1111 Institutional Caster Series

Dersheng Casters Keep Rolling

AQPU (brown round) Wheel Diameter × Wheel Width 125 x 31mm

EAN


YJ-11110500607013

Swivel castor, Single Bolthole Stamping Fork - Ø12.5 Extended control lever surface, Mounting Type - Single Bolthole device Aluminum core, High Quality Polyurethane Wheel Tread Gray, Bearing - Ball Bearing.

Wheel tread: Made of high quality polyurethane

Wheel Center: Aluminum core

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data

Fork Type

● Imperial ○ Metric

Wheel Diameter 5 "

Wheel Width 1-1/4 "

Wheel Bearing Wheels With Ball Bearings

Single Bolt HoleCentre Hole 1/2 "

Offset 1-7/16 "

Swivel Interference 7-13/16 "

Overall Height 6-1/4 "

Swivel Radius 3-15/16 "

Hardness Of Tread 92±5° Shore A

Load Capacity (Dynamic) 507lbs

Load Capacity (Static) 761lbs

Temperature -4°F to +158°F

Swivel Caster

Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 2.1lbs

Standard ISO22883

Advantages at a glance

Rolling Resistance


• • • • •

Operating Noise

• • • • •


Floor Surface Preservation • • • • •

Dimensions





Mounting



 $^{{}^{*}}$ For any deviation between metric and imperial spec, please refer to the metric spec.