

DERSHENG
Dersheng Casters Keep Rolling

Picture may differ from original product

Wheel surface: high-quality elastic rubber
Wheel Center: iron core

Drawings are for reference only and may differ from the product

Advantages at a glance

Rolling Resistance ● ● ● ● ○

Operating Noise ● ● ● ● ●

Floor Surface Preservation ●●●●●

Floor Surface Preservation ●●●●●

Floor Surface Preservation ●●●●●

Floor Surface Preservation ●●●●●

Floor Surface Preservation ●●●●●

Floor Surface Preservation ●●●●●

Floor Surface Preservation ●●●●●

Floor Surface Preservation ●●●●●

Floor Surface Preservation ●●●●●

Floor Surface Preservation ●●●●●

Floor Surface Preservation ●●●●●

Floor Surface Preservation ●●●●●

Floor Surface Preservation ●●●●●

Floor Surface Preservation ●●●●●

Floor Surface Preservation ●●●●●

Floor Surface Preservation ●●●●●

Technical drawing of the roller assembly. The front view (left) shows a circular roller with a diameter of 244 mm and a central hole with a diameter of 200 mm. The side view (right) shows the roller's profile with a width of 53 mm. The roller is mounted on a frame with a central support and a side bracket.

Technical drawing of a rectangular plate with the following dimensions and features:

- Overall width: 144
- Overall height: 105
- Distance from the left edge to the center of the hole: 75
- Distance from the top edge to the center of the hole: 120
- Hole diameter: $\varnothing 13$
- The hole is located in the lower-left quadrant of the plate.

* For any deviation between metric and imperial spec, please refer to the metric spec.