

1120 Single Raceway, Light Duty Caster Series



Bánh MRC (màu trong suốt) Kích thước: Đường kính × Độ rộng 38×16.5mm


EAN

YJ-11200150071013

Rigid Casters, Stamping Fabricated Caster Fork, 36 x 15mm Bolt Hole Spacing Zine-Plated surface, Mounting Type - Top Plate device Reinforced Polypropylene and Wheel Tread Transparent, Bearing—Ball Bearings.

Wheel surface: Thermoplastic (PA6)  
Wheel Center: Thermoplastic (PA6)

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

|                                                                        |                           |
|------------------------------------------------------------------------|---------------------------|
| <input checked="" type="radio"/> Metric <input type="radio"/> Imperial |                           |
| Wheel Diameter                                                         | 38mm                      |
| Wheel Width                                                            | 16.5mm                    |
| Wheel Bearing                                                          | Wheels With Ball Bearings |
| Plate Size                                                             | 46 x 26mm                 |
| Bolt Hole Spacing                                                      | 36 x 15mm                 |
| Plate Hole                                                             | 5mm                       |
| Overall Height                                                         | 50mm                      |
| Hardness Of Tread                                                      | 75±5° Shore D             |
| Load Capacity (Dynamic)                                                | 20kgs                     |
| Load Capacity (Static)                                                 | 30kgs                     |
| Temperature                                                            | -20°C to +80°C            |
| Fork Type                                                              | Rigid Caster              |
| Stainless                                                              | N/A                       |
| Electrical Conductivity                                                | N/A                       |
| Anti-Static                                                            | N/A                       |
| Weight                                                                 | 0.06kgs                   |
| Standard                                                               | ISO22883                  |


Advantages at a glance

|                            |           |
|----------------------------|-----------|
| Rolling Resistance         | ● ● ● ● ● |
| Operating Noise            | ● ● ○ ○ ○ |
| Floor Surface Preservation | ● ● ○ ○ ○ |

Dimensions



Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.