

## 1121 Double Raceway, Light Duty Caster Series



Rubber wheel Wheel diameter × Wheel width 50×20 mm


EAN

YJ-11210200065913

Portable Casters, Threaded Stem Stamping Fork—3/8"-16 teeth Zine-Plated, Mounting Type - Threaded Stem hardware Reinforced Polypropylene Wheel Center, High-Quality Resilient Rubber rim Black, Plain Bearings.

Wheel surface: High-quality elastic rubber  
Wheel Center: Thermoplastic (PA6)

Drawings are for reference only and may differ from the product



Picture may differ from original product

### Technical Data


Imperial  Metric

Wheel Diameter	2 "
Wheel Width	13/16 "
Wheel Bearing	Wheel With Plain Bearing
Threaded Stem	3/8 " -16牙
Threaded Length	1-3/8 "
Offset	1 "
Swivel Interference	4 "
Overall Height	2-9/16 "
Swivel Radius	2 "
Hardness Of Tread	80±5° Shore A
Load Capacity (Dynamic)	77lbs
Load Capacity (Static)	116lbs
Temperature	-4°F to +248°F
Fork Type	Swivel Caster
Stainless	N/A
Electrical Conductivity	N/A
Anti-Static	N/A
Weight	0.4lbs
Standard	ISO22883


### Advantages at a glance

Rolling Resistance	● ● ● ○ ○
Operating Noise	● ● ● ● ○
Floor Surface Preservation	● ● ● ● ○

### Dimensions



### Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.