



1121 Double Raceway, Light Duty Caster Series

Rubber Wheel Diameter × Wheel Width 100 x 24mm


EAN

YJ-11210400062713

Swivel Caster, Top Plate Riveted and Stamping 72 x 53.5mm (2-7/8" x 2-1/8") Bolt Hole Spacing
Zine-Plated, Mounting Type - Top Plate
Reinforced Polypropylene core, High-Quality Resilient Rubber Wheel Tread
Bearing - Plain Bearing

Wheel surface: high-quality elastic rubber
Wheel Center: Thermoplastic (PA6)

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

☒ Imperial ☐ Metric	
Wheel Diameter	4 "
Wheel Width	1 "
Wheel Bearing	Wheel With Plain Bearing
Plate Size	3-11/16 " x 2-15/16 "
Bolt Hole Spacing	2-7/8 " x 2-1/8 "
Plate Hole	3/8 "
Offset	1-3/4 "
Swivel Interference	7-1/2 "
Overall Height	5-1/16 "
Swivel Radius	3-13/16 "
Hardness Of Tread	95±5° Shore A
Load Capacity (Dynamic)	176lbs
Load Capacity (Static)	265lbs
Temperature	-4°F to +248°F
Fork Type	Swivel Caster
Stainless	N/A
Electrical Conductivity	N/A
Anti-Static	N/A
Weight	1.2lbs
Standard	ISO22883


Advantages at a glance

Rolling Resistance	● ● ● ○ ○
Operating Noise	● ● ● ● ○
Floor Surface Preservation	● ● ● ● ○

Dimensions



Mounting



* For any deviation between metric and imperial spec, please refer to the metric spec.