# 1124 1-1/2" Wide General Purposes Caster Series



MRC (Transparent) Wheel Diameter × Wheel Width 100 x 32mm


EAN

YJ-11240400071023

Rigid Caster, Welded Caster Fork 85 x 70mm (3-3/8" x 2-3/4") Bolt Hole Spacing Zine-Plated, Top Plate (4.5T) Mounting Type system Reinforced Polypropylene Wheel Center and Wheel Tread Transparent, Bearing—Ball Bearings.

Wheel tread: Thermoplastic (PA6)
Wheel Center: Thermoplastic (PA6)

Drawings are for reference only and may differ from the product



Picture may differ from original product

### **Technical Data**

● Imperial ○ Metric

Wheel Diameter 4 "

Wheel Width 1-5/16 "

Wheel Bearing Wheels With Ball Bearings

Plate Size 4-9/16 " x 4 "

Bolt Hole Spacing 3-3/8 " x 2-3/4 "

Plate Hole 13/16 " x 3/8 "

Overall Height 5-5/8 "

Hardness Of Tread 75±5° Shore D

Load Capacity (Dynamic) 441lbs

Load Capacity (Static) 661lbs

Temperature -4°F to +176°F

Fork Type Rigid Caster

Stainless N/A

Electrical Conductivity N/A

Electrical Conductivity

Anti-Static

N/A

Weight

2.7lbs

Standard

ISO22883

## Advantages at a glance


Rolling Resistance • •


Operating Noise 

● ● ○ □


Floor Surface Preservation  $\bullet \bullet \circ \circ \circ$ 

### Dimensions





## Mounting



<sup>\*</sup> For any deviation between metric and imperial spec, please refer to the metric spec.