

1124 1-1/2" Wide General Purposes Caster Series

AQPU (grey round) Wheel Diameter × Wheel Width 100 x 40mm


EAN

YJ-11240400602043

Swivel Caster with Riveted Fork and Stamping Fork—85 x 70mm (3-3/8" x 2-3/4") Bolt Hole Spacing Mounting Type
Zine-Plated, Top Plateed (4.5T) Mounting Type system
Aluminum core, High Quality Polyurethane Wheel Tread
Gray, Bearing—Ball Bearings.

Wheel tread: Made of high-quality polyurethane
Wheel Center: aluminum core

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data


Imperial Metric

Wheel Diameter	4 "
Wheel Width	1-5/8 "
Wheel Bearing	Wheels With Ball Bearings
Plate Size	4-9/16 " x 4 "
Bolt Hole Spacing	3-3/8 " x 2-3/4 "
Plate Hole	13/16 " x 3/8 "
Offset	1-3/16 "
Swivel Interference	6-3/8 "
Overall Height	5-5/8 "
Swivel Radius	3-3/16 "
Hardness Of Tread	77±5° Shore A
Load Capacity (Dynamic)	717lbs
Load Capacity (Static)	1075lbs
Temperature	-4°F to +158°F
Fork Type	Swivel Caster
Stainless	N/A
Electrical Conductivity	N/A
Anti-Static	N/A
Weight	3.4lbs
Standard	ISO22883


Advantages at a glance

Rolling Resistance	● ● ● ● ●
Operating Noise	● ● ● ● ●
Floor Surface Preservation	● ● ● ● ●

Dimensions



Mounting



* For any deviation between metric and imperial spec, please refer to the metric spec.