



1124 1-1/2" Wide General Purposes Caster Series

PU (red flat) Wheel Diameter × Wheel Width 125 × 40 mm


EAN

YJ-11240500334033

Side brake Caster with Locking system. Top Plate Riveted and Stamping D-shaped footplate. Hole Zine-Plated, Top Plate (4.5T) Mounting Type system Cast Iron Wheel Center with High Quality Polyurethane tread Red Cast Iron finish, Bearing—Ball Bearing.

Wheel tread: Made of high-quality polyurethane  
Wheel Center: cast iron core

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

|                                                                        |                               |
|------------------------------------------------------------------------|-------------------------------|
| <input checked="" type="radio"/> Imperial <input type="radio"/> Metric |                               |
| Wheel Diameter                                                         | 5 "                           |
| Wheel Width                                                            | 1-5/8 "                       |
| Wheel Bearing                                                          | Wheels With Ball Bearings     |
| Plate Size                                                             | 4-9/16 " x 4 "                |
| Bolt Hole Spacing                                                      | 3-3/8 " x 2-3/4 "             |
| Plate Hole                                                             | 13/16 " x 3/8 "               |
| Offset                                                                 | 1-5/16 "                      |
| Swivel Interference                                                    | 7-9/16 "                      |
| Overall Height                                                         | 6-1/2 "                       |
| Swivel Radius                                                          | 3-13/16 "                     |
| Hardness Of Tread                                                      | 93±5° Shore A                 |
| Load Capacity (Dynamic)                                                | 551lbs                        |
| Load Capacity (Static)                                                 | 827lbs                        |
| Temperature                                                            | -4°F to +158°F                |
| Fork Type                                                              | Swivel Caster With Side Brake |
| Stainless                                                              | N/A                           |
| Electrical Conductivity                                                | N/A                           |
| Anti-Static                                                            | N/A                           |
| Weight                                                                 | 5.8lbs                        |
| Standard                                                               | ISO22883                      |


Advantages at a glance

|                            |           |
|----------------------------|-----------|
| Rolling Resistance         | ● ● ● ○ ○ |
| Operating Noise            | ● ● ● ● ○ |
| Floor Surface Preservation | ● ● ● ● ○ |

Dimensions



Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.