



1124 1-1/2" Wide General Purposes Caster Series

SX Rubber Wheel Diameter × Wheel Width 193 x45mm


EAN

YJ-11240800034123

Side brake Caster with Locking system. Top Plate Riveted and Stamping - D-shaped. Hole Zine-Plated, Top Plate (4.5T) Mounting Type system Cast Iron Wheel Center with High-Quality Resilient Rubber tread Iron black, Bearing - Ball Bearing.

Wheel Tread: high-quality elastic rubber
Wheel Center: cast iron core

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

☒ Imperial ☐ Metric	
Wheel Diameter	7-11/16 "
Wheel Width	1-13/16 "
Wheel Bearing	Wheels With Ball Bearings
Plate Size	4-9/16 " x 4 "
Bolt Hole Spacing	3-3/8 " x 2-3/4 "
Plate Hole	13/16 " x 3/8 "
Offset	1-13/16 "
Swivel Interference	11-5/16 "
Overall Height	9-1/2 "
Swivel Radius	5-5/8 "
Hardness Of Tread	80±5° Shore A
Load Capacity (Dynamic)	573lbs
Load Capacity (Static)	860lbs
Temperature	-4°F to +248°F
Fork Type	Swivel Caster With Side Brake
Stainless	N/A
Electrical Conductivity	N/A
Anti-Static	N/A
Weight	8.8lbs
Standard	ISO22883


Advantages at a glance

Rolling Resistance	● ● ● ○ ○
Operating Noise	● ● ● ● ○
Floor Surface Preservation	● ● ● ● ○

Dimensions



Mounting



* For any deviation between metric and imperial spec, please refer to the metric spec.