# 1139 39 Series US Standard Bracket Series



PPR wheel(black) wheel diameter × wheel width 75 x 31mm

EAN

### YJ-11390300261024

Fixed castors, one-piece stamped footrest - advanced holes
Surface electroplating, bottom plate installation device
Impact-resistant polypropylene wheel core, thermoplastic elastomer (TPR) wheel tread
(wheel tread Added thermoplastic shrink film protection)
Black, wheel bearings - precision ball.

Wheel tread: Thermoplastic rubber elastomer (TPR)
Wheel core: Made of high-quality impact-resistant polypropylene

Product descriptions are for reference only. The actual product shall prevail.



Picture may differ from original product

### **Technical Data**

	Metric	0	Imperial
--	--------	---	----------

Wheel Diameter 75mm
Wheel Width 31mm

Wheel Bearing wheel equipped with ball bearings

Plate size 92 x 62mm

Base plate hole spacing 75 x 45mm

Plate hole 12 x 9mm

Overall height 105.5mm

Hardness of tread 82±5° Shore A

Load capacity (dynamic) 90kgs

Load capacity (static) 135kgs

Temperature -20°C to +60°C


Stand StylefixedStainless steelN/AConductiveN/AAntiN/AWeight0.4kgsStandardISO22883


### Advantages at a glance

Rolling Resistance	• • • • 0
Operating Noise	• • • • 0


Floor Surface Preservation • • • • •

#### **Dimensions**





## Mounting



Drawings are for reference only and may differ from the product.

 $<sup>\</sup>ensuremath{^{*}}$  For any deviation between metric and imperial spec, please refer to the metric spec.