1139 39 Series US Standard Bracket Series

ERSHENGDersheng Casters Keep Rolling

Rubber wheel wheel diameter × wheel width 100 x 30.5mm

EAN

YJ-11390400061013

Fixed caster, one-piece stamped foot frame - high-grade holes Galvanized surface, base plate mounting device Thermoplastic plastic wheel core, high-quality elastic rubber wheel surface Wheel - mid-tube

Wheel surface: high quality elastic rubber Wheel core: Thermoplastic (PA6)

Product descriptions are for reference only. The actual product shall prevail.



Picture may differ from original product

Technical Data

● Metric ○ Imperial

Wheel Diameter 100mm
Wheel Width 30.5mm

Wheel Bearing wheels with a central tube

Plate size 92 x 62mm

Base plate hole spacing 75 x 45mm

Plate hole 12 x 9mm

Overall height 130mm

Hardness of tread 80±5° Shore A

Load capacity (dynamic) 80kgs
Load capacity (static) 120kgs

Temperature -20°C to +120°C

Stand StylefixedStainless steelN/AConductiveN/AAntiN/AWeight0.63kgsStandardISO22883

Advantages at a glance

Rolling Resistance

• • • • • •


Operating Noise

• • • • •


Floor Surface Preservation

• • • • •

Dimensions



Mounting



Drawings are for reference only and may differ from the product.

 $[\]boldsymbol{\ast}$ For any deviation between metric and imperial spec, please refer to the metric spec.