

1139 Medium Duty General Purposes Caster Series



Rubber Wheel Diameter × Wheel Width 125 x 30.5mm


EAN

YJ-11390500065023

Swivel Caster, thread-Riveted Stamping Fork—1/2"-13"
Zine-Plated, Mounting Type - Threaded Stem
Reinforced Polypropylene core, High-Quality Resilient Rubber Wheel Tread
Bearing –tube-type

Wheel surface: high-quality elastic rubber
Wheel Center: Thermoplastic (PA6)

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

☒ Metric ☐ Imperial	
Wheel Diameter	125mm
Wheel Width	30.5mm
Wheel Bearing	Wheel With Plain Bearing
Threaded Stem	1/2 " -13
Threaded Size	25mm
Offset	38mm
Swivel Interference	202mm
Overall Height	154mm
Swivel Radius	101mm
Hardness Of Tread	80±5° Shore A
Load Capacity (Dynamic)	90kgs
Load Capacity (Static)	135kgs
Temperature	-20°C to +120°C
Fork Type	Swivel Caster
Stainless	N/A
Electrical Conductivity	N/A
Anti-Static	N/A
Weight	0.99kgs
Standard	ISO22883


Advantages at a glance

Rolling Resistance	● ● ● ○ ○
Operating Noise	● ● ● ● ○
Floor Surface Preservation	● ● ● ● ○

Dimensions



Mounting



* For any deviation between metric and imperial spec, please refer to the metric spec.