

1148 48 48 Series Central Locking Caster Series (All Plastic)



Resolute Rubber wheel (White dark gray) Wheel Diameter x Wheel Width 150 x 15mm


EAN

YJ-11480600458040

Short Stem Central Locking, Total Brake castor. Single Bolthole Stamping Fork Wheel Fork polyamide - white, Mounting Type - Single Bolthole High-quality Impact Resistance Polypropylene Wheel Center,High-Quality Thermoplastic Rubber (TPR) Wheel Tread White dark grey, Bearing - Ball Bearing.

Wheel tread: Thermoplastic rubber elastomer (TPR)
Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

☒ Metric ☐ Imperial	
Wheel Diameter	150mm
Wheel Width	75mm
Wheel Bearing	Wheels With Ball Bearings
Diameter	32mm
Stem Hole Spec	50mm
Offset	47.5mm
Swivel Interference	254mm
Overall Height	155mm
Swivel Radius	127mm
Hardness Of Tread	72±5° Shore A
Load Capacity (Dynamic)	150kgs
Load Capacity (Static)	225kgs
Temperature	-20°C to +60°C
Fork Type	Swivel Caster With Total Brake
Stainless	N/A
Electrical Conductivity	N/A
Anti-Static	N/A
Weight	1.23kgs
Standard	ISO22881


Advantages at a glance

Rolling Resistance	• • • • •
Operating Noise	• • • • •
Floor Surface Preservation	• • • • •

Dimensions



Mounting



* For any deviation between metric and imperial spec, please refer to the metric spec.