1151D Heavy Duty 1.5" Wide General Purposes Caster Series

Dersheng Casters Keep Rolling

PU (Red arc) Wheel Diameter × Wheel Width 100 x 34mm

EAN

YJ-11510400331023

Rigid Caster with integral Stamping Fork and D-shaped hole. Zine-Plated, Top Plate (3.5T) Mounting Type system. Cast Iron Wheel Center with High Quality Polyurethane tread. Red Cast Iron finish, Ball Bearing.

Wheel tread: Made of high-quality polyurethane

Wheel Center: cast iron core

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data

● Imperial ○ Metric

Wheel Diameter 4 "

Wheel Width 1-3/8 "

Wheel Bearing Wheels With Ball Bearings

Plate Size 4-11/16 " x 3-13/16 "

Bolt Hole Spacing 3-3/8 " x 2-3/4 "

Plate Hole 13/16 " x 3/8 "

Overall Height 5-3/16 "

Hardness Of Tread 93±5° Shore A

Load Capacity (Dynamic) 441lbs

Load Capacity (Static) 661lbs

Temperature -4°F to +158°F

Fork Type Rigid Caster

Stainless N/A
Electrical Conductivity N/A

Anti-Static N/A

Weight 2.8lbs

Standard ISO22883

Advantages at a glance

Rolling Resistance


 \bullet \bullet \circ \circ


Operating Noise

• • • 0


Floor Surface Preservation • • • • • •

Dimensions





Mounting



^{*} For any deviation between metric and imperial spec, please refer to the metric spec.