



1168 Levelling Caster Series

AQPU (brown round) Wheel Diameter × Wheel Width 100 x 40mm


EAN

YJ-11680400602073

Swivel Caster with Riveted, Stamping Fork and European standard holes. Zine-Plated, Mounting Type - Top Plate with Height Adjustable Stand. Aluminum Wheel Center with High Quality Polyurethane tread. Brown, Bearing with Ball Bearing.

Wheel Tread: high quality polyurethane  
Wheel Center: aluminum core

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

|                                                                        |                           |
|------------------------------------------------------------------------|---------------------------|
| <input checked="" type="radio"/> Imperial <input type="radio"/> Metric |                           |
| Wheel Diameter                                                         | 4 "                       |
| Wheel Width                                                            | 1-5/8 "                   |
| Wheel Bearing                                                          | Wheels With Ball Bearings |
| Plate Size                                                             | 4-3/16 " x 3-7/16 "       |
| Bolt Hole Spacing                                                      | 3-3/16 " x 2-7/16 "       |
| Plate Hole                                                             | 3/8 " x 23/64 "           |
| Offset                                                                 | 3-1/16 "                  |
| Swivel Interference                                                    | 10 "                      |
| Overall Height                                                         | 5-11/16 "                 |
| Swivel Radius                                                          | 5 "                       |
| Hardness Of Tread                                                      | 92±5° Shore A             |
| Load Capacity (Dynamic)                                                | 551lbs                    |
| Load Capacity (Static)                                                 | 2205lbs                   |
| Temperature                                                            | -4°F to +158°F            |
| Fork Type                                                              | Swivel Caster             |
| Stainless                                                              | N/A                       |
| Electrical Conductivity                                                | N/A                       |
| Anti-Static                                                            | N/A                       |
| Weight                                                                 | 4.2lbs                    |
| Standard                                                               | ISO22883                  |


Advantages at a glance

|                            |           |
|----------------------------|-----------|
| Rolling Resistance         | ● ● ● ● ● |
| Operating Noise            | ● ● ● ● ● |
| Floor Surface Preservation | ● ● ● ● ● |

Dimensions



Mounting



\* For any deviation between metric and imperial spec, please refer to the metric spec.