

PU Series

Wheel Diameter x Wheel Width 138 x 40mm

EAN

YJ-12033355156101

Excellent Floor Surface Preservation and wear resistance, low noise.
Excellent Hydrolysis Resistance.
Suitable for tropical regions and humid working environments.
PU Red.



Wheel Center: cast iron core
Wheel Tread: High-quality polyurethane
Bearings: —

Drawings are for reference only and may differ from the product

Picture may differ from original product

Technical Data

Imperial Metric

Wheel Diameter(D) 5-1/2 "

Wheel Width(T2) 1-5/8 "

Wheel Bearing Without Bearing

Axle Bore(d) —

Axle Bore(S) 1-5/8 "

Bearing Bore Depth(t) 1/2 "

Hub Length(T1) 1-5/8 "

Hardness Of Tread 92±5° Shore A

Load Capacity (Dynamic) 772lbs

Load Capacity (Static) 1157lbs

Temperature -4°F to +158°F

Electrical Conductivity N/A

Anti-Static N/A


Weight 3.0lbs

Standard ISO22883

Advantages at a glance

Rolling Resistance	● ● ● ○ ○
Operating Noise	● ● ● ● ○
Floor Surface Preservation	● ● ● ● ○

2D Dimensional Drawing of Single Wheel



* For any deviation between metric and imperial spec, please refer to the metric spec.

© Copyright 2025 Dersheng International www.dersheng.com