

PU Series



Wheel Diameter × Wheel Width 138 x 60mm


EAN

YJ-12033355256101

Excellent Floor Surface Preservation and wear resistance, low noise.
Excellent Hydrolysis Resistance.
Suitable for tropical regions and humid working environments.
PU Red

Wheel Center: cast iron core
Wheel Tread: High-quality polyurethane
Bearings: —

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

☒ Metric ☐ Imperial	
Wheel Diameter(D)	138mm
Wheel Width(T2)	60mm
Wheel Bearing	Without Bearing
Axle Bore(d)	
Axle Bore(S)	52mm
Bearing Bore Depth(t)	22mm
Hub Lenth(T1)	68mm
Hardness Of Tread	92±5° Shore A
Load Capacity (Dynamic)	560kgs
Load Capacity (Static)	840kgs
Temperature	-20°C to +70°C
Electrical Conductivity	N/A
Anti-Static	N/A
Weight	2.92kgs
Standard	ISO22883

Advantages at a glance

Rolling Resistance	● ● ● ○ ○
Operating Noise	● ● ● ● ○
Floor Surface Preservation	● ● ● ● ○

2D Dimensional Drawing of Single Wheel



* For any deviation between metric and imperial spec, please refer to the metric spec.