

QPU Series

QPU (Grey flat) Wheel Diameter x Wheel Width 100 x 34mm

YJ-12035304136401

Excellent elasticity, reduced push resistance, improved machine controllability, and Excellent Wear Resistant.
Excellent Hydrolysis Resistance.
Suitable for use in tropical regions and humid working environments.
QPU Gray



Wheel Tread: cast iron core
Wheel Center: High-quality polyurethane
Bearing: —

Drawings are for reference only and may differ from the product

Picture may differ from original product

Technical Data

| |
|--|
| <input checked="" type="radio"/> Imperial <input type="radio"/> Metric |
| Wheel Diameter(D) 4 " |
| Wheel Width(T2) 1-3/8 " |
| Wheel Bearing Without Bearing |
| Axle Bore(d) |
| Axle Bore(S) 1-3/8 " |
| Bearing Bore Depth(t) 3/8 " |
| Hub Length(T1) 1-3/8 " |
| Hardness Of Tread 77±5° Shore A |
| Load Capacity (Dynamic) 485lbs |
| Load Capacity (Static) 728lbs |
| Temperature -4°F to +158°F |
| Electrical Conductivity N/A |
| Anti-Static N/A |
| Weight 1.4lbs |
| Standard ISO22883 |

Advantages at a glance

| | |
|----------------------------|---------|
| Rolling Resistance | • • • • |
| Operating Noise | • • • • |
| Floor Surface Preservation | • • • • |

2D Dimensional Drawing of Single Wheel

* For any deviation between metric and imperial spec, please refer to the metric spec.

© Copyright 2025 Dersheng International www.dersheng.com