

AQPU Series



Wheel Diameter × Wheel Width 75 x 30mm


EAN

YJ-12036003135400

It has good elasticity, reduces pushing resistance, improves machine controllability, and has good wear resistance.  
It has excellent Hydrolysis Resistance.  
Suitable for tropical regions and humid working environments.  
QPU Gray Wheel Surface Curved

Wheel Center: Aluminum core  
Wheel Tread: High-quality polyurethane  
Bearings: —

Drawings are for reference only and may differ from the product



Picture may differ from original product


Technical Data

|                                                                        |                 |
|------------------------------------------------------------------------|-----------------|
| <input checked="" type="radio"/> Imperial <input type="radio"/> Metric |                 |
| Wheel Diameter(D)                                                      | 3 "             |
| Wheel Width(T2)                                                        | 1-3/16 "        |
| Wheel Bearing                                                          | Without Bearing |
| Axle Bore(d)                                                           | —               |
| Axle Bore(S)                                                           | 1-1/8 "         |
| Bearing Bore Depth(t)                                                  | 3/8 "           |
| Hub Lenth(T1)                                                          | 1-5/16 "        |
| Hardness Of Tread                                                      | 92±5° Shore A   |
| Load Capacity (Dynamic)                                                | 353lbs          |
| Load Capacity (Static)                                                 | 529lbs          |
| Temperature                                                            | -4°F to +158°F  |
| Electrical Conductivity                                                | N/A             |
| Anti-Static                                                            | N/A             |
| Weight                                                                 | 0.4lbs          |
| Standard                                                               | ISO22883        |

Advantages at a glance

|                            |           |
|----------------------------|-----------|
| Rolling Resistance         | • • • • • |
| Operating Noise            | • • • • • |
| Floor Surface Preservation | • • • • • |

2D Dimensional Drawing of Single Wheel



\* For any deviation between metric and imperial spec, please refer to the metric spec.