## **Product Information Sheet**

# **XPU Series**

Wheel Diameter × Wheel Width 185 x 70mm

EAN

YJ-12036107280103

Excellent Mechanical Properties, maintaining Heavy Load during high-speed movement; good wear resistance; not easily deformed.

Excellent resistance to chemicals, solvents, and corrosion.


Suitable for Forklift Trucks, electric Forklift Trucks, Heavy duty machines, AGVs, and

automated industrial applications. XPU Burgundy

Wheel Center: Iron core

Wheel Tread: High-quality polyurethane

Product descriptions are for reference only. The actual product shall prevail.



Dersheng Casters Keep Rolling

Picture may differ from original product

#### **Technical Data**

Wheel centre/ rim

Standard

<ul><li>Imperial O Metric</li><li>Wheel Diameter (D)</li></ul>	7-3/8
Wheel Width (T2)	2-13/16 "
Wheel installation — Hub Lenth (T1)	2-7/16 "
Wheel Mounting Bore Diameter	1-5/8 "
Keyway Width	1/2 "
Wheel Keyway Depth (H)	43.3
Load Capacity (Static)	3307lbs
Load Capacity at 4 km/h	220lbs
Load Capacity at 6 km/h	1874lbs
Load Capacity at 10 km/h	1543lbs
Load Capacity at 16 km/h	400kgs
Hardness Of Tread	92±5° Shore A
Temperature	-4°F to +158°F


Tread Pattern


Iron core/galvanized Non-Marking Conductive N/A Anti N/A Weight 19.7lbs

### Advantages at a glance

Rolling Resistance **Operating Noise** Floor Surface Preservation • • • • •

## 2D Dimensional Drawing of Drive Wheel





ISO22883

<sup>\*</sup> For any deviation between metric and imperial spec, please refer to the metric spec.