Product Information Sheet

XPU Series

Wheel Diameter × Wheel Width 230 x 82mm

EAN

YJ-12036109336100

Excellent Mechanical Properties, maintaining Heavy Load during high-speed movement; good wear resistance; not easily deformed.

Excellent resistance to chemicals, solvents, and corrosion.


Suitable for Forklift Trucks, Electric Stackers, Heavy duty machines, AGVs, and automated

industrial applications. XPU, Brown, Curved Wheel Surface

Wheel Center: cast iron core

Wheel Tread: High-quality polyurethane

Product descriptions are for reference only. The actual product shall prevail.



Dersheng Casters Keep Rolling

Picture may differ from original product

Technical Data

● Metric ○ Imperial	
Wheel Diameter (D)	230mm
Wheel Width (T2)	82mm
Wheel installation — Hub Lenth (T1)	_
Wheel center-bore diameter (d)	45mm
Wheel Mounting Bolt Hole PCD Diameter	14mm
Wheel Mounting Bolt Hole PCD	70mm
# Of Wheel mounting bolt boles	5
Wheel mounting bolt hole (M)	10
Number of wheel mounting bolt holes	3
Load Capacity (Static)	2400kgs
Load Capacity at 4 km/h	1600kgs
Load Capacity at 6 km/h	1360kgs
Load Capacity at 10 km/h	1120kgs

Load Capacity at 16 km/h 640kgs Hardness Of Tread 92±5° Shore A -20°C to +70°C Temperature

Tread Pattern

Cast iron / sprayed with Wheel centre/ rim


anti-rust oil


Non-Marking Υ Conductive N/A Anti N/A 6.24kgs Weight ISO22883 Standard

Advantages at a glance

Rolling Resistance **Operating Noise** Floor Surface Preservation • • • • •

2D Dimensional Drawing of Drive Wheel





^{*} For any deviation between metric and imperial spec, please refer to the metric spec.