Product Information Sheet

XPU Series

Wheel Diameter × Wheel Width 300 x 120mm

EAN

YJ-12036112480303

Excellent Mechanical Properties, maintaining Heavy Load during high-speed movement; good wear resistance; not easily deformed.

Excellent resistance to chemicals, solvents, and corrosion.

Suitable for Forklift Trucks, electric Forklift Trucks, Heavy duty machines, AGVs, and

automated industrial applications.

XPU Burgundy

Wheel Center: Iron core

Wheel Tread: High-quality polyurethane

Product descriptions are for reference only. The actual product shall prevail.



Dersheng Casters Keep Rolling

Picture may differ from original product

Technical Data

● Metric ○ Imperial	
Wheel Diameter (D)	300mm
Wheel Width (T2)	120mm
Wheel installation — Hub Lenth (T1)	140mm
Wheel Mounting Bore Diameter	40mm
Keyway Width	12mm
Wheel Keyway Depth (H)	43.3mm
Load Capacity (Static)	4050kgs
Load Capacity at 4 km/h	2700kgs
Load Capacity at 6 km/h	2295kgs
Load Capacity at 10 km/h	1890kgs
Load Capacity at 16 km/h	1080kgs
Hardness Of Tread	92±5° Shore A
Temperature	-20°C to +70°C

Tread Pattern


Iron core/galvanized Wheel centre/ rim


Non-Marking Conductive N/A Anti N/A 31.25kgs Weight Standard ISO22883

Advantages at a glance

Rolling Resistance **Operating Noise** Floor Surface Preservation • • • • •

2D Dimensional Drawing of Drive Wheel





^{*} For any deviation between metric and imperial spec, please refer to the metric spec.