

QPU Series


Wheel Diameter × Wheel Width 250 x 58mm

EAN

YJ-12036310230103

Good elasticity, reduces pushing resistance, improves machine controllability, and has good wear resistance.
 Excellent Hydrolysis Resistance.
 Suitable for tropical regions and humid working environments.
 QPU Blue

Wheel Center: Iron core
 Wheel Tread: High-quality polyurethane



Picture may differ from original product

Product descriptions are for reference only. The actual product shall prevail.


Technical Data

<input checked="" type="radio"/> Metric <input type="radio"/> Imperial	
Wheel Diameter (D)	250mm
Wheel Width (T2)	58mm
Wheel installation — Hub Lenth (T1)	—
Wheel center-bore diameter (d)	122mm
Wheel Mounting Bolt Hole PCD Diameter	6.6mm
Wheel Mounting Bolt Hole PCD	63mm
# Of Wheel mounting bolt boles	12
Wheel mounting bolt hole (M)	12
Number of wheel mounting bolt holes	2
Load Capacity (Static)	975kgs
Load Capacity at 4 km/h	650kgs
Load Capacity at 6 km/h	552.5kgs
Load Capacity at 10 km/h	455kgs
Load Capacity at 16 km/h	260kgs
Hardness Of Tread	87±5° Shore A
Temperature	-20°C to +70°C
Tread Pattern	—
Wheel centre/ rim	Iron core/galvanized
Non-Marking	Y
Conductive	N/A
Anti	N/A
Weight	14.12kgs
Standard	ISO22883

Advantages at a glance

Rolling Resistance	•••••
Operating Noise	•••••
Floor Surface Preservation	•••••

2D Dimensional Drawing of Drive Wheel



* For any deviation between metric and imperial spec, please refer to the metric spec.