1129 Medical Caster Series

Dersheng Casters Keep Rolling

PPR (Pearlescent dark gray) Wheel Diameter × Wheel Width 125 x 31mm

EAN


YJ-X11290500267013

Swivel castor, Single Bolthole Stamping Fork - Ø12.5 Surface Zine-Plated, Mounting Type - Single Bolthole device High-quality Impact Resistance Polypropylene Wheel Center, High-Quality Thermoplastic Rubber (TPR) Wheel Tread Pearl-colored dark gray, Bearing - Ball Bearing.

Wheel tread: Thermoplastic rubber elastomer (TPR)

Wheel Center: Made of high-quality impact-resistant polypropylene

Drawings are for reference only and may differ from the product



Picture may differ from original product

Technical Data

● Imperial ○ Metric

Wheel Diameter 5 "

Wheel Width 1-1/4"

Wheel Bearing Wheels With Ball Bearings

Single Bolt HoleCentre Hole 1/2 "

Offset 1-1/2 "

Swivel Interference 8 "

Overall Height 6-7/16 "

Swivel Radius 4 "

Hardness Of Tread 82±5° Shore A

Load Capacity (Dynamic) 220lbs

Load Capacity (Static) 331lbs

Temperature -4°F to +140°F
Fork Type Swivel Caster

Stainless N/A

Electrical Conductivity N/A

Anti-Static N/A

Weight 1.5lbs

Standard ISO22883

Advantages at a glance

Rolling Resistance


 \bullet \bullet \bullet \circ

Operating Noise


 \bullet \bullet \bullet \circ

Floor Surface Preservation • • • • •

Dimensions



Mounting



 $^{{}^{*}}$ For any deviation between metric and imperial spec, please refer to the metric spec.